Sign in

web page requesting between client server and

Search

Advanced Scholar Search Scholar Preferences

**Scholar** Articles and patents

anvtime

include citations

Create email alertResults 31 - 40 of about 2,430. (0.14 sec)

#### A decision support system for tuning **Web** servers in distributed object oriented network architectures

gatech.edu (DOC)

RD van der Mei. WK Ehrlich, PK Reeser. ... - ACM SIGMETRICS ..., 2000 - portal acm.org

... The **Web Server** test configuration is shown in Figure 4. The top left machine in the first row represents the Web Server under Test ... 61 Page 6. ... Figure 5 shows the predicted and empirical residence times for several transaction request rates for dataset IV, and Table 1 shows the ...

Cited by 12 - Related articles - All 4 versions

## Fine-Grained Parallelism in Dynamic Web Content Generation: The Parse and Dispatch Approach

psu.edu (PDF)

S Papastavrou, G Samaras, P Evripidou, P ... - On The Move to .... 2003 - Springer

... Meanwhile, the parent process continues execution free to accept Page 5. ... Once a worker thread has served its assigned **request**, it places itself back to the **thread** pool. ... In popular **Web** servers, the pre-configured size of the **thread** pool ranges from five to twenty. ...

Cited by 4 - Related anticles - Bt. Direct - All 11 versions

## Pavilion: a middleware framework for collaborative **Web**-based applications

psu.edu (PDF)

PK McKinley, AM Malenfant, JM ... - Proceedings of the ..., 1999 - portal acm.org

... Proxy plug-ins enable the application to define type-specific processing of files that takes place after the browser **request** but before the ... Page 6. ... shares the address space of the other Pavilion components, which is different than the address space used by the **web** browser, the ...

Cited by 29 - Related articles - All 7 versions

# [boc] Performance of **Web** servers in a distributed computing environment

vuni (DOC)

WK Ehrlich, R Hariharan, PK Reeser, RD Van ... - ... Engineering in the ..., 2001 - math.vu.nl ... SSO instance is created at the start of a user's session, and each scripting page accessed by ...

and location models, and lead to different performance models depending on the Web server implementation. ... T. Since the TSO only lives during the course of a single request, there is ...

Cited by 7 - Related articles - View as HTML - All 4 versions

# PerfExplorer: A performance data mining framework for large-scale parallel computing

KA Huck, AD Malony - 2005 - computer.org

... For example, the PerfExplorer client has been configured to be launched from a web browser, with no prior installation or configuration of the ... Currently, the user can request correlation analysis of events or met-rics, the result of which will help guide the selection of per ... Page 7. ...

Cited by 46 - Related articles - All 16 versions

psu.edu (PDF)

### SCTP: an innovative transport layer protocol for the web

P Natarajan, JR Iyengar, PD Amer, R ... - ... on World Wide Web, 2006 - portal acm.org

... Page 6. blocking among the response for the most recent GET request and the responses for previous requests transmitted on the same SCTP ... The experiment topology, shown in Figure 4, uses three nodes: a custom web client (FreeBSD 5.4) and an Apache server (FreeBSD ...

Cited by 16 - Related articles - All 18 versions

#### Evaluation of edge caching/offloading for dynamic content delivery

C Yuan, Y Chen, Z Zhang - ... conference on World Wide Web, 2003 - portal.acm.org

... The presentation tier gathers the user input and translates the user **request** into a processing action at the business layer. ... The back end servers provide **page** fragments and composition frameworks. The entire **Web page** is assembled at the offloading destination. ...

Cited by 39 - Related articles - Bt. Direct - All 19 versions

#### End to End Performance Modeling of Web Server Architectures

R Hadharan, WK Ehrlich, D Cura, PK ... - ACM SIGMETRICS ..., 2000 - portal.acm.org

... The script-engine (SE) dynamics generally depend on the **Web server** implementation and on the OS. ... 58 **Page** 3. ... 3. If the SE-LQ if full, then the transaction **request** is rejected, the **client** receives a "connection refused" message, and the TCP connection is torn down. ...

Cited by 4 - Related articles - All 4 versions

#### [PDF] A Comparison of Portable Dynamic Web Content Technologies for the Apache Server

G Gousios, D Spinellis - SANE, 2002 - Citeseer

... 8 **Page** 9. ... The response size to each **request** was 73,5 kb, a typical size for modern **web** sites. If the response does not arrive in a period of 3 seconds, the whole process group is killed. ... BENCH3 was responsible to start **threads** that perform a single **request** and then die. ...

Cited by 15 - Related articles - All 9 versions


#### A hybrid **web server** architecture for secure e-business **web** applications

V Beltran, D Carrera, J Guitart, J Torres, E ... - High Performance ..., 2005 - Springer

... a timeout assimilated to the amount of time a human **client** would expect a reply from its **web** browser before considering a **page request** failed ... Specification and implementation of dynamic **web** site benchmarks, 2002 ... A hybrid **web server** architecture for e-commerce applications ...

Offed by 3 - Related articles - PL Direct - All 14 versions

# Create email alert



Search

Result Page: **Previous** 1 2 3 4 5 6 7 8 9 1011 1213 Next

web page requesting between client

<u> psu.edu</u> (PDF)

usb.ve (DOC)

psu.edu (POF)

<u>psuedu</u> (PDF)

 $\underline{\text{Go to Google Home}} \cdot \underline{\text{About Google}} \cdot \underline{\text{About Google Scholar}}$ 

©2010 Google